

Alfa Laval Unique Vacuum Breaker Valve

Control/Check Valves

Introduction

The Alfa Laval Unique Vacuum Breaker Valve is a CIP-able pneumatic check valve that ensures positive pressure, thereby eliminating vacuum conditions on the downstream side of high-temperature, short-time (HTST) pasteurization piping and systems.

Its compact, modular and hygienic design meets the highest process demands in terms of hygiene and safety. Built on the well-proven Alfa Laval Unique SSSV small single seat valve, it features a fast-acting actuator and a single air connection to enable Cleaning-in-Place (CIP).

It can also be fitted with the Alfa Laval ThinkTop® V50 for sensing and control unit of the valve. Few moving parts ensure easy maintenance, high reliability, and low total cost of ownership.

Applications

The Unique Vacuum Breaker Valve is designed to prevent vacuum conditions in hygienic high-temperature, short-time pasteurization systems across the dairy, food, beverage industries.


Benefits

- Designed for convenient and effective CIP
- Compact, fast-acting and fully automated valve
- Exceptional valve hygiene and cleanability
- Authorized to carry the 3-A symbol

Standard design

The Unique Vacuum Breaker Valve consists of a stainless steel valve body, seals, actuator, a rotating internal ball that moves up and down inside the valve chamber, and clamp rings.

Certificates



Working principle


The Alfa Laval Unique Vacuum Breaker Valve operates in a manner similar to a ball check valve. When pipelines are pressurized during a process or CIP, the internal ball is forced upward against its seat, closing the vent port (Fig. A).

When pipeline pressure drops, the ball is drawn downward, allowing air to enter the vent, thereby preventing vacuum in the system (Fig. B).



During CIP, a pneumatic actuator is used (pulsed) to force the ball off the upper seat, enabling the seat and the interior of the vacuum breaker valve to be cleaned. CIP fluid is discharged during the actuator pulse and is drained through the vent port (Fig. C).

Working Principle



TECHNICAL DATA

Pressure

Valve

| | |
|---------------------------|-------------|
| Maximum product pressure: | 10 bar |
| Minimum product pressure: | Full vacuum |

Actuator

| | |
|-----------------------|-------|
| Maximum air pressure: | 7 bar |
| Minimum air pressure: | 5 bar |

Temperature

| | |
|--------------------|-----------------|
| Temperature range: | -10 °C to 90 °C |
|--------------------|-----------------|

PHYSICAL DATA

Materials

Valve/Actuator

| | |
|-----------------------------|------------------|
| Product wetted steel parts: | AISI 316L |
| Product wetted seals: | EPDM |
| Ball: | Polypropylene HD |
| Internal surface finish: | Ra ≤0.8 μm |

Actuator

| | |
|--------------------------|---------|
| Seals: | NBR |
| External surface finish: | Blasted |

Connections


| | |
|-----------------|---------------|
| Compressed air: | 6 mm |
| Vent: | ½" Tri-Clamp |
| Process/CIP: | 1½" Tri-Clamp |

Ordering

Please state the following when ordering:

- Unique SSV Vacuum Breaker
- Wetted elastomer preference
- Control Top

Dimensions (mm)



| Size | 38 mm |
|----------------|-------|
| A | 208 |
| B | 56 |
| D ¹ | 57 |
| E | 54 |
| Weight (kg.) | 1.85 |

This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval AB (publ) or any of its affiliates (jointly "Alfa Laval"). No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

How to contact Alfa Laval

Up-to-date Alfa Laval contact details for all countries are always available on our website at www.alfalaval.com